

DECLARATION OF PERFORMANCE

Nro. 085-FF-2015-04-14

1. **Unique identification code of the product-type:** Extruded polystyrene (XPS) Finnfoam FK-29 170mm.
2. **Allowing identification of the construction product:** EAN-Code: 64 18711 59170 2
3. **Intended uses of the construction product:** Products are used as thermal insulation. Product applications are specified in the web site www.finnfoam.fi.

4. **Name, registered trade name and contact address of the manufacturer:**

Finnfoam Oy (0689386-6)
Satamakatu 5
24100 Salo, Finland
Tel. +358 2 777 300
Fax: +358 2 777 3020
Email: finnfoam@finnfoam.fi

6. **System of attestation of conformity:** AVCP 3
7. **Declaration of performance concerning a construction product covered by a harmonized standard:**

VTT Expert Services (NB. 0809) and Institute of thermal insulation of Vilnius Gediminas Technical University (NB. 1688) performed initial type testing under system 3 and issued test/calculation reports.

FINNFOAM[®]
MAAN PARAS ERISTE

9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	F	EN 13164:2012
Long term water absorption by total immersion	NPD	
Long term water absorption by diffusion	NPD	
Release of dangerous substances	No releases	
Thermal resistance R_D (m ² K)/W	5,50	
Thermal conductivity λ_D W/(mK)	0,031	
Thickness	T1	
Water vapour transmission	NPD	
Compressive strength	NPD	
Tensile strength	NPD	
Dimensional stability	DS(23,90)	
Freeze-thaw resistance	NPD	
Compressive creep	NPD	

Safety data sheet: www.finnfoam.fi/kayttoturvallisuustiedote

Signed for and on behalf of the manufacturer by:

Henri Nieminen, CEO

Salo 14.4.2015



(signature)